



Product data sheet

Triflex Liquid Thixo (Stellmittel flüssig)

Use

Used as a liquid thickening / thixotropic agent for addition to Triflex PMMA products.

Properties

- Increases the viscosity where required

Components

Component	Product
Thixotropic agent	Triflex Liquid Thixo

Packaging

Component	Pack size
Triflex Liquid Thixo	Canister: 500ml

Colour(s)

Translucent brown.

Mixing ratio

Up to 1% by weight depending on desired thixotropy.

Mixing instructions

- Evenly mix the Triflex Liquid Thixo into the PMMA base resin;
- Leave to stand for approximately 20 minutes for thixotropy to develop;
- Mix product in accordance to the Product Data Sheet.

Tool cleaning

Clean tools with Triflex Cleaner.

Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 12 months.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.



Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.