



## DETAIL WATERPROOFING



- TRIFLEX CRYL FINISH 205 @ 0.50 Kg/m<sup>2</sup> MIN.
- TRIFLEX PRODETAIL® @ 3.00 Kg/m<sup>2</sup> MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- GENERIC SUBSTRATE (PREPARED)




## GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

## INDICATIVE SYSTEM BUILD-UP



## SYSTEM

TRIFLEX PRODETAIL® WITH SMOOTH FINISH

## PROJECT

STANDARD

## DETAIL

DETAIL WATERPROOFING

## DRAWING NUMBER

PRODETAIL\_SF\_001\_DETAIL WATERPROOFING

## SCALE

NTS

## DATE

26/06/2018

**Triflex**

Delivering solutions together.

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS