



DETAIL WATERPROOFING



- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- GENERIC SUBSTRATE (PREPARED)

NOTES

- 1 CAPPING INSTALLED / REINSTATED AFTER WATERPROOFING APPLICATION
- 2 TRIFLEX PROFIBRE® @ 3.00 Kg/m² MIN. TO ENCAPSULATE FIXING HEADS




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX PRODETAIL®

PROJECT

STANDARD

DETAIL

UPSTAND WITH SECRET FIXED CAPPING - WATERPROOFING BENEATH CAPPING

DRAWING NUMBER

PRODETAIL_017_UPSTAND WITH SECRET FIXED CAPPING -WATERPROOFING BENEATH CAPPING


SCALE
NTS

DATE
26/06/2018

Triflex
Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS