




## DETAIL WATERPROOFING



## NOTES

- 1 SOLVENT FREE MASTIC SEALANT
- 2 TRIFLEX PROFIBRE® @ 3.00 Kg/m<sup>2</sup> MIN.  
APPLIED IN TWO APPLICATIONS @ 1.50 Kg/m<sup>2</sup> MIN. AT 90° TO ONE ANOTHER




ROOFS | ROOF DETAILS | REPAIRS

## GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

## INDICATIVE SYSTEM BUILD UP



## SYSTEM

TRIFLEX PRODETAIL® WITH SMOOTH FINISH

## PROJECT

STANDARD

## DETAIL

GUTTER JOINT

## DRAWING NUMBER

PRODETAIL\_SF\_060\_GUTTER JOINT

## SCALE

NTS

## DATE

19/02/2015

**Triflex**

Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
 ST15 8JS | Tel: 01785 819119  
[www.triflex.co.uk](http://www.triflex.co.uk) | [info@triflex.co.uk](mailto:info@triflex.co.uk)