



### DETAIL WATERPROOFING




### DETAIL WATERPROOFING (HEAVY DUTY)



### NOTES

- 1 TRIFLEX CRYL PASTE OR TRIFLEX FLEXFILLER
- 2 OVERBAND TO EXTEND A MINIMUM 75mm EITHER SIDE OF CRACK / DAY JOINT



### GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

### INDICATIVE SYSTEM BUILD-UP



### SYSTEM

TRIFLEX PRODETAIL® WITH HEAVY DUTY FINISH

### PROJECT

STANDARD

### DETAIL

OVERBANDING CRACK / DAY JOINT GREATER THAN 1mm

### DRAWING NUMBER

PRODETAIL\_HD\_312  
\_OVERBANDING CRACK\_DAY  
JOINT GREATER THAN 1mm

SCALE  
NTS

DATE  
26/06/2018

**Triflex**  
Delivering solutions together.

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS