



DETAIL WATERPROOFING



- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- OUTLET LINER / SPIGOT (PREPARED)
- GENERIC SUBSTRATE


DETAIL WATERPROOFING (HEAVY DUTY)



- TRIFLEX CRYL FINISH 205 @ 0.60 Kg/m² MIN.
- TRIFLEX PRODETAIL® @ 1.50 Kg/m² MIN. WITH TRIFLEX QUARTZ (0.7 - 1.2mm) @ 5.00 Kg/m² APPROX.
- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- GENERIC SUBSTRATE (PREPARED)

NOTES

- 1** LIFT OUTLET COVER / GUARD TO ALLOW FOR PREPARATION, PRIMING AND WATERPROOFING INSTALLATION AND REINSTATE



GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.



SYSTEM

TRIFLEX PRODETAIL® WITH HEAVY DUTY FINISH

PROJECT

STANDARD

DETAIL

WADE TPYE OUTLET WITH LEAF / DEBRIS GUARD

DRAWING NUMBER

PRODETAIL_HD_106_WADE TYPE_OUTLET WITH LEAF _DEBRIS GUARD

SCALE	DATE
NTS	26/06/2018



ROOFS | ROOF DETAILS | REPAIRS

Triflex
Delivering solutions together.

Triflex (UK) Limited
Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk