


DETAIL WATERPROOFING



TRIFLEX CRYL FINISH 205 @ 0.50 Kg/m² MIN.

TRIFLEX PRODETAIL[®] @ 3.00 Kg/m² MIN.

TRIFLEX 110g REINFORCEMENT FLEECE

TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)

GENERIC SUBSTRATE (PREPARED)


NOTE: HEAVY DUTY WEARING LAYER MAY BE EXTENDED ONTO VERTICAL / INCLINED SURFACES (IF REQUIRED)

GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX PRODETAIL[®] WITH HEAVY DUTY FINISH

PROJECT

STANDARD

DETAIL

DETAIL WATERPROOFING

DRAWING NUMBER

PRODETAIL_HD_001_DETAIL WATERPROOFING

SCALE

NTS

DATE

26/06/2018

Triflex

Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS