



### DETAIL WATERPROOFING



### NOTES

- 1 TRIFLEX PRODETAIL® @ 1.50 Kg/m² MIN. WITH TRIFLEX QUARTZ (0.7 - 1.2mm) @ 5.00 Kg/m² APPROX. TO CREATE AN IMPACT RESISTANT KEY. ALLOW TO CURE AND REMOVE EXCESS QUARTZ.
- 2 COPING BEDDED ON QUARTZ FILLED LAYER WITH SUITABLE MORTAR / ADHESIVE



### GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

### INDICATIVE SYSTEM BUILD-UP



### SYSTEM

TRIFLEX PRODETAIL®

### PROJECT

STANDARD

### DETAIL

UPSTAND WITH COPING - WATERPROOFING BENEATH COPING

### DRAWING NUMBER

PRODETAIL\_011\_UPSTAND WITH COPING -WATERPROOFING BENEATH COPING

### SCALE

NTS

### DATE


25/06/2018

**Triflex**

Delivering solutions together.

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS