



## Product data sheet

# Triflex Than Primer L 1K (Than Grund L 1K)

### Use

Single component primer for concrete and cementitious substrates prior to installation of Triflex marking systems.

### Properties

- Low viscosity
- High penetration
- Improves adhesive and cohesive strength
- Sprayable
- Alkali-resistant
- Resistant to de-icing salts, petrol and diesel

### Components

Component	Product
Primer	Triflex Than Primer L 1K

### Packaging

Component	Pack size
Primer	Canister: 9L

### Colour

Transparent brown.

### Application conditions

Condition	Value
Ambient and substrate temperature	5°C to +35°C
Relative atmospheric humidity	60%
Dew point	3°C above dew point

### Substrate assessment / pretreatment / preparation

Remove existing markings, paint, finishes etc. incompatible with overlay by grinding or blasting, and abrade metals to create a key.

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Specification.

### Application method

Airless or compressed air based spray application or roller.

### Consumption

Approximately 0.20Kg/m<sup>2</sup> minimum.

Density: 0.94g/cm<sup>3</sup>

**Note:** Consumption based on smooth, even, non-absorbent substrate.



### Drying time (at 20°C)

Condition	Time
Can be re-coated after	Approximately 20 - 30 minutes

**Note:** Times will be increased at lower temperatures and reduced at higher temperatures.

### Tool cleaning

Clean tools with Triflex Cleaner.

### Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 12 months.

### Health and safety

Refer to Safety Data Sheets.

### Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

### Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.