

Product data sheet

Triflex Colour Mix[®]



Use

Decorative, coloured mix used as part of the Triflex Colour Design surface finish.

Packaging

Component	Pack size
Colour Mix	Drum: 10.00Kg

Colour(s)

Triflex Colour Mix Colour	Triflex Ceryl Finish 205 Colour
A719 Grey	7030 Quartz 03
A720 Blue	5081 Opal 03
A721 Grey blue	5092 Opal 02
A722 Grey green	7030 Quartz 03
A725 Red orange	1001 Amber 02
A727 Cream beige	1001 Amber 02
A728 Anthracite grey	7043 Slate 03
A729 Stone red	8081 Ruby 01

Application conditions

Refer to Triflex Ceryl Finish 205 application conditions as shown below:

Condition	Value
Ambient and substrate temperature	0°C to +35°C
Relative atmospheric humidity	Up to 95%
Dew point	3°C above dew point

Avoid broadcasting Triflex Colour Mix where windy conditions will affect the finished aesthetic of the product.

Substrate assessment / pretreatment / preparation

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Specification proposal.

Application method

Refer to Triflex Specification proposal - Spray into wet Triflex Ceryl Finish 205 using a Hopper spray gun with the Triflex Colour Mix attachment.

Note: Ensure that the colour of the Triflex Colour Mix matches the finish colour - refer to Colours.

Consumption

0.80 (800g/m²) - 1.00Kg/m²

Note: Consumption based on smooth, even substrate.

Storage

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Health and safety

Refer to Safety Data Sheets.



Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.