



Product data sheet

Triflex Primer 620 AP

Use

Primer and adhesion promoter for use with Triflex SmartTec and Triflex RoofTec

Properties

- Cold liquid applied
- Fast drying
- Easy application

Components

Component	Product
Resin	Triflex Primer 620 AP

Packaging

Component	Pack size
Resin	Canister: 1.25L

Colour(s)

- Orange / brown

Application conditions

Condition	Value
Ambient and substrate temperature	+5°C to +30°C
Relative atmospheric humidity	Up to 95%
Dew point	3°C above dew point

Substrate assessment / pretreatment / preparation

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Specification.

Application method

Brush or roller

Note: Use masking tape to avoid staining of adjacent substrate.

Consumption

0.09 - 0.10 Kg/m² – refer to Triflex Specification.

Note: Consumption based on smooth, even, non-absorbent substrate. Two applications are required on vertical surfaces.

Curing time (at 20°C)

Condition	Time
Can be over-coated	Approximately 10 minutes

Interruptions during works

If work is interrupted for more than 12 hours or if soiled by rain etc., use Triflex Cleaner to clean and reactivate the transition area. Overlay after Triflex Cleaner has evaporated and a minimum 20 minutes / maximum 60 minutes after application.

Tool cleaning

Clean tools with Triflex Cleaner.

Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 6 months.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.