

# Triflex Bitumen Blocker



## Use

Primer for Triflex SmartTec only for bituminous substrates to eliminate bitumen staining / bleeds.

## Properties

- Cold liquid applied
- Easy to apply
- Solvent free
- Odour free

## Components

Component	Product
Primer	Triflex Bitumen Blocker

## Packaging

Component	Pack size
Triflex Bitumen Blocker	Drum: 10.00Kg

## Colour(s)

- Transparent

## Application conditions

Condition	Value
Ambient and substrate temperature	10°C to +30°C
Relative atmospheric humidity	Up to 60%
Dew point	3°C above dew point

## Substrate assessment / pretreatment / preparation

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Specification proposal.

## Initial resin mixing / decanting

Thoroughly mix the primer in the drum with a paint stirrer until a smooth, uniform consistency is achieved.

## Application method

Roller.

## Consumption

0.40Kg/m<sup>2</sup> (400g/m<sup>2</sup>).

**Note:** Consumption based on smooth, even, non-absorbent substrate.



## Curing time

Condition	Time
Rainproof	Approximately 4 hours
Overcoat	Approximately 4 hours

**Note:** Times will be increased at lower temperatures and reduced at higher temperatures. Overcoat when primer turns from milky to clear.

## Tool cleaning

Clean tools with Triflex Cleaner.

## Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 12 months.

## Health and safety

Refer to Safety Data Sheets.

## Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

## Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.