



## MAIN AREA WATERPROOFING



## NOTES

- 1 LIFT OUTLET COVER / GUARD TO ALLOW FOR PREPARATION, PRIMING AND WATERPROOFING INSTALLATION AND REINSTATE
- 2 TRIFLEX METAL PRIMER @ 0.08 - 0.10 ltr/m<sup>2</sup> MIN.




## GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

## INDICATIVE SYSTEM BUILD-UP



## SYSTEM

TRIFLEX PROTECT® WITH HEAVY DUTY FINISH

## PROJECT

STANDARD

## DETAIL

FIXFAST TYPE OUTLET WITH LEAF / DEBRIS GUARD

## DRAWING NUMBER


PROTECT\_HD\_111\_FIXFAST  
TYPE\_OUTLET WITH LEAF  
\_DEBRIS GUARD

SCALE	DATE	REVISION
NTS	22/03/2019	A

**Triflex**  
Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS