



MAIN AREA WATERPROOFING



NOTES

- 1 LIFT OUTLET COVER / GUARD TO ALLOW FOR PREPARATION, PRIMING AND WATERPROOFING INSTALLATION AND REINSTATE
- 2 TRIFLEX METAL PRIMER @ 0.08 - 0.10 ltr/m² MIN.




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX PROTECT® WITH COLOURED FINISH

PROJECT

STANDARD

DETAIL

FIXFAST TYPE OUTLET WITH LEAF / DEBRIS GUARD

DRAWING NUMBER

PROTECT_CF_111_FIXFAST
TYPE_OUTLET WITH LEAF
_DEBRIS GUARD

SCALE	DATE	REVISION
NTS	20/03/2019	A

Triflex
Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk

ROOFS | ROOF DETAILS | REPAIRS