



## DETAIL WATERPROOFING




## MAIN AREA WATERPROOFING



## NOTES

- 1 STAR CUT REINFORCEMENT FLEECE AROUND FIXINGS AND MAKE GOOD WITH TRIFLEX CRYL PASTE
- 2 TRIFLEX PROFIBRE® @ 3.00 Kg/m² MIN. APPLIED IN TWO APPLICATIONS @ 1.50 Kg/m² MIN. TO ENCAPSULATE FIXINGS




## GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

## INDICATIVE SYSTEM BUILD-UP



## SYSTEM

TRIFLEX PROTECT® WITH COLOURED FINISH

## PROJECT

STANDARD

## DETAIL

SURFACE MOUNTED DETAIL  
>25mm

## DRAWING NUMBER

PROTECT\_CF\_057\_SURFACE  
MOUNTED DETAIL GREATER  
THAN 25MM

## SCALE

NTS

## DATE

20/03/2019


## REVISION

A

**Triflex**  
Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



ROOFS | ROOF DETAILS | REPAIRS