



Product data sheet

Triflex ProDrain Primer

Use

Triflex ProDrain Primer is a deep-penetrating, moisture-resistant primer that protects Triflex ProDrain Fix+ from dehydration.

Properties

2-component primer with a polymer dispersion base. Triflex ProDrain Primer offers the following features:

- Solvent-free
- Easy to use
- Prevents shrinkage cracks
- Improves adhesion

Components

Component	Product
Primer	Triflex ProDrain Primer

Packaging

Component	Pack size
Primer	Plastic canister: 5.00Kg

Mixing instructions

Triflex ProDrain Primer is diluted with water with a mixing ratio of 1:3.

Note: No catalyst is required.

Application method

Apply Triflex ProDrain Primer with a universal roller.

Consumption

Approx. 0.15l/m² minimum.

Conditions for use

Triflex ProDrain Primer can be applied at substrate and ambient temperatures between +10 °C and +35 °C. Can also be used in interior applications.

Mineral substrates can be recoated after approx. 10 - 15 minutes. The white control colour provides surface control after application. If this colour or a moist primer base is no longer visible, a new coat of Triflex ProDrain Primer must be applied.

Storage / shelf life

Can be stored unopened and unmixed for approx. 6 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.



Substrate assessment / pretreatment / preparation

The substrate must be prepared by grinding and thoroughly sweep and vacuum. In all cases, ensure that the prepared surface is clean, dry and free from dust, laitance, grease, oil and other contaminants. Minimum tensile adhesion strength: 1.0 N/mm².

During application, the surface temperature must be at least 7°C above dew point. If it falls below this threshold, a separating film of moisture can form on the surface to be processed.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.