



Product data sheet

Triflex 110g Reinforcement Fleece

Use

Polyester fleece used with Triflex resins in Triflex fully and partially reinforced systems.

Properties

- High tensile strength
- Provides thickness control

Packaging

Component	Available widths
50lm rolls	100mm
	150mm
	200mm
	262mm
	350mm
	525mm
	700mm
	1050mm

Available shapes (special shapes can be produced to order)

- Inside corner
- Outside corner
- 80mm pipe corner
- 110mm pipe corner
- 135mm pipe corner

Colour

White with Triflex logo

Application conditions

Refer to resin used with reinforcement.

Application method

Apply as even layer of embedment resin in accordance with the specification and immediately embed the Triflex 110g reinforcement fleece into the wet resin, pressing trapped air free using the roller. Immediately apply a further layer of resin in accordance with the specification wet-on-wet ensuring the reinforcement is fully encapsulated.

Consumption

Ensure a 50mm overlap between reinforcement strips (100mm if left over 12 hours) for Triflex PMMA and PU resins. For Triflex RoofTec ensure a 50mm overlap between reinforcement strips (150mm if left over 12 hours).

Storage

Store in a dry place and protect from moisture.



Disposal information

Recommended EWC waste codes:

- Non contaminated fleece: 20 01 11 textiles
- Fleece contaminated with resin (dried): 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
- Fleece contaminated with resin (moist and will not dry): 17 09 03 other construction and demolition wastes (including mixed wastes) containing hazardous substances

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.